

PRODUCT INFORMATION AND PRICE LIST

Currency: USD MOQ: Free

**Power Amplifier DSP Series(2 ohms)**

DSP series amplifier have reliable quality, huge output power, best tone. LED panel have level, power voltage and channel temperature display. It can change fan speed according to the channel temperature, ensure the cooling well. It can protect the amplifier when over heat or un-normal voltage.

Suitable for gymnasium, band, showplace, dancer and disco.



Model	DSP-400	DSP-600	DSP-800	DSP-1000	DSP-1200	DSP-1400
<b>Unit Price</b>	<b>\$272.00</b>	<b>\$327.00</b>	<b>\$367.00</b>	<b>\$530.00</b>	<b>\$552.50</b>	<b>\$568.00</b>
Stereo (8ohm)	2x400W	2x600W	2x800W	2x1000W	2x1200W	2x1400W
Stereo (4ohm)	2x650W	2x950W	2x1300W	2x1600W	2x1800W	2x2100W
Stereo (2ohm)	2x950W	2x1400W	2x1900W	2x2400W	2x2700W	2x3000W
Bridge (8ohm)	1300W	1900W	2600W	3200W	3600W	4200W
Bridge (4ohm)	1900W	2800W	3800W	4800W	5400W	6000W
Output Circuit Type	Class H					
Input Impedance	20Kohm					
Frequency Response	20Hz ~ 20KHz					
THD	<0.05%					
Slew Rate	80V/us					
Hum and Noise	103db					
Damp Modulus	>500					
Radiator	High/Low Automatism control					
Safeguard	DC safeguard/overloading/boot-strap short test					
Power Supply	AC100~120V/200-240V 50~60Hz					
Gross Weight	28.00KGS	30KGS	32.00KGS	38KGS	39KGS	41.00KGS

**NETWORK Power Amplifier DSP-B Series(2 ohms)**

DSP-B Series professional network power amplifier adopted 24 Bit professional DSP audio CMOS chip. It is designed for long distance audio system; It is preferred for Gymnasium and Large-scan audio system.

Model	DSP-B200	DSP-B400	DSP-B600	DSP-B800
<b>Unit Price</b>	<b>\$438.80</b>	<b>\$477.00</b>	<b>\$515.00</b>	<b>\$555.00</b>
Stereo (8ohm)	2X200W	2X400W	2X600W	2X800W
Stereo (4ohm)	2X350W	2X700W	2X1050W	2X1350W
Stereo (2ohm)	2X500W	2X1000W	2X1400W	2X1800W
Bridge (8ohm)	650W	1250W	1750W	2300W
Bridge (4ohm)	950W	1700W	2300W	2900W
Output Circuit	Class AB			Class H
Frequency Response	5Hz ~ 50KHz			
THD	<0.05%			
Slew Rate	40V/us			
Input Impedance	20Kohm			
Signal Noise Ratio	>103dB			
Damp Modulus	>400			
Radiator	High/low Automatism control			
Gross Weight	21KGS	25KGS	28KGS	29KGS



## 4CH Power Amplifier C Series(2 ohms)

Inner 4 high quality amplifiers in 1 power amplifier. It has reasonable structure, can meet the occasion which need multi-channels.

Model	C-4200	C-4250	C-4300	C-4350
<b>Unit Price</b>	<b>\$233.00</b>	<b>\$270.00</b>	<b>\$290.00</b>	<b>\$292.00</b>
Stereo (8ohm)	4X200W	4X250W	4X300W	4X350W
Stereo (4ohm)	4X300W	4X370W	4X450W	4X500W
Stereo (2ohm)	4X400W	4X480W	4X580W	4X650W
Output Circuit	Class AB			
Frequency Response	5Hz ~ 50KHz			
THD	<0.05%			
Slew Rate	40V/us			
Input Impedance	20Kohm			
Signal Noise Ratio	>103dB			
Damp Modulus	>400			
Radiator	High/low Automatism control			
Gross Weight	25KGS	26KGS	27KGS	28KGS



## 3CH Power Amplifier H Series

3 way Naphon H series professional power amplifier include all the specifications of Naphon power amplifier, It also have subwoofer crossover.it has two main channels and one subwoofer channel, easy for adjust.it has enough power for subwoofer channel to meet lots of different requirements.it ensure your performance more professional, easily and freely

Model	H-250	H-350
<b>Unit Price</b>	<b>\$253.00</b>	<b>\$303.00</b>
Stereo (8ohm)	2x250W+500W	2X350W+700W
Stereo (4ohm)	2X400+800W	2X550W+1000W
Frequency Response	20Hz ~ 20KHz: +0/-0.3dB	
Input Impedance	20Kohm	
Cross Point	50-250Hz	
THD	≤0.05%	≤0.08%
SNR	>104db	>103db
Slew Rate	60V/us	75V/us
Damping Factor	400	450
Output Circuit	Class AB	
Power Supply	AC100~120V/200~240V 50~60Hz	
G.W.	25KGS	27KGS



## Power Amplifier PA Series

PA series Power Amplifier is the smaller 1U professional amplifier. It has perfect sound, sharp appearance and reasonable structure; It has complete protect function. It might use with the conference system etc.

Model	PA-100	PA-200
<b>Unit Price</b>	<b>\$122.00</b>	<b>\$143.00</b>
Stereo (8ohm)	2x100W	2x200W
Stereo (4ohm)	2x70W	2x130W
Frequency Response	5Hz ~ 50KHz: +0/-0.3dB	
Input Impedance	20Kohm	
THD	≤0.05%	
SNR	>104dB	
Slew Rate	40V/us	
Damping Factor	400	
Output Circuit	Class AB	
Power Supply	AC100~120V/200~240V 50~60Hz	
G.W.	11KGS	12KGS



## Power Amplifier MH Series(2 ohms)



### FEATURES

- ◆ Working modes: stereo/bridge/mono
- ◆ Cooling Mode: 2-Speed Fan
- ◆ Indicators: Power/Signal/Clip
- ◆ Standard XLR and 1/4" TRS sockets
- ◆ Load Protection: DC Safeguard/Output Overloading/Start-up/Boot-strap Short Test
- ◆ Adopt bulky power supply, effectively reduce the intermodulation distortion and noise

Model	MH-400	MH-600	MH-800	MH-1000	MH-1200	MH-1400
<b>Unit Price</b>	<b>\$260.80</b>	<b>\$315.00</b>	<b>\$355.00</b>	<b>\$477.00</b>	<b>\$497.00</b>	<b>\$517.00</b>
Stereo (8ohm)	2x400W	2x600W	2x800W	2x1000W	2x1200W	2x1400W
Stereo (4ohm)	2x650W	2x950W	2x1300W	2x1600W	2x1800W	2x2100W
Stereo(2ohm)	2x950W	2x1400W	2x1900W	2x2400W	2x2700W	2X3000W
Rated Bridged (8ohm)	1300W	1900W	2600W	3200W	3600W	4200W
Rated Bridged (4ohm)	1900W	2800W	3800W	4800W	5400W	6000W
Output Circuit	Class H					
Frequency Response	20Hz ~ 20KHz: +0/-3dB					
Input impedance	20kohm					
THD	0.50%					
Slew Rate	80V/usec					
Hum and Noise	103db					
Damp Modulus	500					
Radiator	High/Low Automatism control					
Power Supply	AC100~120V/200~240V 50~60Hz					
Gross Weight	27.00kgs	29.00kgs	30.00kgs	37.00kgs	38kgs	40kgs
Dimensions	48.20X44.30X13.20cm			48.2x46.8x13.2cm		

## VU Power Amplifier B Series(2 ohms)



### FEATURES

- ◆ Working modes: stereo/bridge/mono
- ◆ Cooling Mode: 2-Speed Fan
- ◆ Indicators: Power/Signal/Clip
- ◆ Standard XLR and 1/4" TRS sockets
- ◆ The unit has built-in digital current limiter protection
- ◆ Load Protection: DC Safeguard/Output Overloading/Start-up/Boot-strap Short Test

Model	B-200	B-300	B-400	B-500	B-600	B-800	B-1000	B-1200
<b>Unit Price</b>	<b>\$185.50</b>	<b>\$205.50</b>	<b>\$235.00</b>	<b>\$245.00</b>	<b>\$255.00</b>	<b>\$320.00</b>	<b>\$369.00</b>	<b>\$409.00</b>
Stereo (8ohm)	2x200W	2x300W	2x400W	2x500W	2x600W	2x800W	2x1000W	2x1200W
Stereo (4ohm)	2x350W	2x500W	2x700W	2x850W	2x1050W	2x1350W	2x1700W	2x1900W
Stereo(2ohm)	2X500W	2x800W	2X1000W	2X1300W	2X1400W	2X1800W	2X2200W	2X2400W
Rated Bridged (8ohm)	650W	1000W	1250W	1460W	1750W	2300W	2900W	3000W
Rated Bridged (4ohm)	950W	1300W	1700W	1920W	2300W	2900W	3800W	4000W
Input Impedance	20Kohm							
Frequency Response	5Hz-50KHz							
THD	0.05%							
Slew Rate	40V/usec							
Hum Noise	103db							
Damp Modulus	>400							
Radiator	High/Low Automatism control							
Safeguard	DC safeguard/out overloading/boot-strap short test							
Power Supply	AC100~120V/200~240V 50~60Hz							
Gross Weight	22.00kgs	25kgs	26.00kgs	27kgs	28.5kgs	30kgs	38.00kgs	40.00kgs
Dimensions	56X55X17cm				56x55x22cm			

## Power Amplifier MA Series(20hms)

### FEATURES

- ◆ Working modes: stereo/bridge/mono
- ◆ Cooling Mode: 2-Speed Fan
- ◆ Indicators: Power/Signal/Clip
- ◆ Standard XLR and 1/4" TRS sockets
- ◆ The unit has built-in digital current limiter protection
- ◆ Load Protection: DC Safeguard/Output Overloading/Start-up/Boot-strap Short Test



Model	MA-200	MA-300	MA-400	MA-500	MA-600	MA-800	MA-1000	MA-1200
<b>Unit Price</b>	<b>\$189.90</b>	<b>\$212.00</b>	<b>\$235.00</b>	<b>\$249.00</b>	<b>\$260.80</b>	<b>\$325.00</b>	<b>\$377.00</b>	<b>\$418.00</b>
Stereo (8ohm)	2x200W	2x300W	2x400W	2x500W	2x600W	2x800W	2x1000W	2x1200W
Stereo (4ohm)	2x350W	2x500W	2x700W	2x850W	2x1050W	2x1350W	2x1700W	2x1900W
Stereo(2ohm)	2X500W	2x800W	2X1000W	2X1300W	2X1400W	2X1800W	2X2200W	2X2400W
Rated Bridged (8ohm)	650W	1000W	1250W	1460W	1750W	2300W	2900W	3000W
Rated Bridged (4ohm)	950W	1300W	1700W	1920W	2300W	2900W	3800W	4000W
Input Impedance	20Kohm							
Frequency Response	5Hz ~ 50KHz: +0/-3dB							
THD	0.0005							
Slew Rate	40v/usec							
Hum and Noise	103db							
Dam Modulus	>400							
Radiator	High/Low Automatism control							
Safeguard	DC safeguard/out overloading/boot-strap short test							
Power Supply	AC100~120V/200~240V 50~60Hz							
Gross Weight	22.00kgs	25kgs	26.00kgs	27kgs	28.5kgs	30kgs	38.00kgs	40.00kgs
Dimensions	48.20X45.50X88.8cm						48.2x45.5x13.2cm	

## Power Amplifier SA Series

SA series amplifier have reliable quality, huge output power, best tone. Suitable for gymnasium, band, showplace, dancer and disco.

Model	SA-200	SA-300	SA-500	SA-600
<b>Unit Price</b>	<b>\$155.00</b>	<b>\$178.80</b>	<b>\$228.00</b>	<b>\$248.00</b>
Stereo (8ohm)	2x250W	2x350W	2x500W	2x650W
Stereo (4ohm)	2x400W	2x550W	2x800W	2x950W
BTL	650W	900W	1250W	1650W
Frequency Response	20Hz ~ 20KHz			
THD	<0.05%			
IMD	<0.05%			
Slew Rate	100V/us			
Input Impedance	50Kohm			
Signal Noise Ratio	>105dB			
Input Sensitivity	0.775V			
Height	2U			
Gross Weight	24.00KGS	27.00KGS	29.00KGS	31.50KGS
Dimensions	54.60x58.00x19.00cm			





# Power Amplifier XP Series(2 ohms)

XP series amplifier have reliable quality, huge output power, best tone. Suitable for gymnasium, band, showplace, dancer and disco.



Model	XP-400	XP-600	XP-800	XP-1000	XP-1200	XP-1400
<b>Unit Price</b>	<b>\$255.00</b>	<b>\$313.00</b>	<b>\$350.50</b>	<b>\$485.00</b>	<b>\$505.00</b>	<b>\$525.00</b>
Stereo (8ohm)	2x400W	2x600W	2x800W	2x1000W	2x1200W	2x1400W
Stereo (4ohm)	2x650W	2x950W	2x1300W	2x1600W	2x1800W	2x2100W
Stereo (2ohm)	2x950W	2x1400W	2x1900W	2x2400W	2x2700W	2x3000W
Bridge (8ohm)	1300W	1900W	2600W	3200W	3600W	4200W
Bridge (4ohm)	1900W	2800W	3800W	4800W	5400W	6000W
Output Circuit Type	Class H					
Input Impedance	20Kohm					
Frequency Response	20Hz ~ 20KHz					
THD	<0.05%					
Slew Rate	80V/us					
Hum and Noise	103db					
Damp Modulus	>500					
Radiator	High/Low Automatism control					
Safeguard	DC safeguard/overloading/boot-strap short test					
Power Supply	AC100~120V/200-240V 50~60Hz					
Gross Weight	28.00KGS	30KGS	32.00KGS	38KGS	39KGS	41.00KGS

# Power Amplifier K Series

## FEATURES

- ◆ Working modes: stereo/bridge/mono
- ◆ Cooling Mode: 2-Speed Fan
- ◆ Indicators: Power/Signal/Clip
- ◆ Standard XLR and 1/4" TRS sockets
- ◆ Load Protection: DC Safeguard/Output Overloading/Start-up/Boot-strap Short Test
- ◆ Adopt bulky power supply, effectively reduce the intermodulation distortion and noise

Model	K-150	K-300	K-500	K-750
<b>Unit Price</b>	<b>\$145.00</b>	<b>\$180.00</b>	<b>\$238.00</b>	<b>\$288.80</b>
Stereo (8ohm)	2x150W	2x300W	2x500W	2x750W
Stereo (4ohm)	2x250W	2x450W	2x750W	2x1200W
Rated Bridged (8ohm)	300W	600W	1000W	1500W
S/N	>100db			
Frequency Response	20Hz ~ 20KHz: +0/-3dB			
Input Sensitivity	1.0V			
Power Supply	AC100~120V/200~240V 50~60Hz			
Gross Weight	17kgs	18.00kgs	26kgs	31kgs
Dimensions	58.50X57X15cm			



# Power Amplifier HI Series

## FEATURES

- ◆ Working modes: stereo/bridge/mono
- ◆ Cooling Mode: 2-Speed Fan
- ◆ Indicators: Power/Signal/Clip
- ◆ Standard XLR and 1/4" TRS sockets
- ◆ Load Protection: DC Safeguard/Output Overloading/Start-up/Boot-strap Short Test
- ◆ Adopt bulky power supply, effectively reduce the intermodulation distortion and noise



Model	HI-200	HI-300	HI-400	HI-500	HI-600	HI-800
<b>Unit Price</b>	<b>\$165.00</b>	<b>\$180.00</b>	<b>\$210.00</b>	<b>\$230.00</b>	<b>\$268.00</b>	<b>\$313.00</b>
Stereo (8ohm)	2x200W	2x300W	2x400W	2x500W	2x600W	2x800W
Stereo (4ohm)	2x350W	2x500W	2x700W	2x850W	2x1050W	2x1350W
Rated Bridged (8ohm)	650W	1000W	1250W	1450W	1750W	2300W
Rated Bridged (4ohm)	950W	1300W	1700W	1900W	2300W	2900W
Frequency Response	50Hz ~ 50KHz: +0/-3dB					
Input Sensitivity@8ohm	1.0V					
Power Supply	AC100~120V/200~240V 50~60Hz					
Gross Weight	26.50kgs	28.00kgs	30.50kgs	33.00kgs	35.50kgs	38.50kgs
Dimensions	48.20X40.30X13.20cm			48.20X45.30X13.20cm		

# Power Amplifier J Series

Features includes: Two Channels, it can be bridged; Time-delay starting protection and protections for the overloading, over temperature, short circuit, load etc;Level indicator in 2 x4 LED, status indicator for power, bridge and protection;2 fans for cooling; Power/signal and clip indicate; Protected by DC safeguard output, overloading, start-up boot-strap short test.

Model	J-150	J-250	J-400	J-550	J-800
<b>Unit Price</b>	<b>\$125.50</b>	<b>\$158.00</b>	<b>\$228.00</b>	<b>\$288.00</b>	<b>\$328.00</b>
Output Power (8ohm)	2x150W	2x250W	2x400W	2x550W	2x800W
Output Power (4ohm)	2x250W	2x450W	2x750W	2x1200W	2x1600W
Rated Bridged (8ohm)	300W	500W	700W	1100W	1600W
S/N	>100db				
Frequency Response	18Hz ~ 20KHz +/-3db				
Input Sensitivity@80hm	1.0V				
Height	2U				
Gross Weight	17kgs	18kgs	26kgs	29kgs	31.00kgs
Dimensions	58X58X16cm				



# Power Amplifier R Series

R series amplifier have reliable quality, huge output power, best tone. Suitable for gymnasium, band, showplace, dancer and disco.



Model	R-150	R-300	R-500	R-600	R-800	R-1000
<b>Unit Price</b>	<b>\$145.00</b>	<b>\$180.00</b>	<b>\$238.80</b>	<b>\$268.80</b>	<b>\$325.00</b>	<b>\$365.00</b>
Stereo (8ohm)	2x150W	2x300W	2x500W	2x600W	2x800W	2x1000W
Stereo (4ohm)	2x250W	2x450W	2x750W	2x900W	2x1200W	2x1600W
Bridge (8ohm)	300W	600W	1000W	1200W	1600W	2000W
Output Circuit Type	Class H					
Input Impedance	20Kohm					
Frequency Response	20Hz ~ 20KHz					
THD	<0.05%					
Slew Rate	80V/us					
Hum and Noise	100db					
Damp Modulus	>500					
Radiator	High/Low Automatism control					
Safeguard	DC safeguard/overloading/boot-strap short test					
Power Supply	AC100~120V/200~240V 50~60Hz					
Gross Weight	19KGS	20KGS	24KGS	28KGS	30KGS	32KGS

## KTV Amplifier KA Series

KA series amplifier have reliable quality, best tone.  
Suitable for Karaoke room etc.

<b>Model</b>	<b>KA-310</b>
<b>Unit Price</b>	<b>\$66.00</b>
Output power	2x120W
Mic input sensitivity	10mv
Input sensitivity	200mv
S/N	>95db
Frequency	20Hz-20KHz
Microphone Tone	80Hz+/-12db;12KHz+/-12db
Echo Tone	250Hz+/-12db,12KHz+/-12db
Over all Tone	80Hz+/-12db;2.5KHz+/-8db;2KHz+/-12db
Dimension	420x375x140mm



## KTV Amplifier KA Series

KA series amplifier have reliable quality, best tone.  
Suitable for Karaoke room etc.

<b>Model</b>	<b>KA-200</b>
<b>Unit Price</b>	<b>\$183.00</b>
Output power	2x200W
Mic input sensitivity	10mv
Input sensitivity	150mv
S/N	>95db
Frequency	20Hz-20KHz
Microphone Tone	80Hz+/-12db;12KHz+/-12db
Echo Tone	250Hz+/-12db,12KHz+/-12db
Over all Tone	80Hz+/-12db;2.5KHz+/-8db;2KHz+/-12db
Dimension	500x445x210mm



## KTV DSP Amplifier DSP Series

DSP series amplifier have reliable quality, best tone.  
Suitable for Karaoke room etc.

<b>Model</b>	<b>DSP-200</b>
<b>Unit Price</b>	<b>\$206.80</b>
Output power	2x200W
Mic input sensitivity	10mv
Input sensitivity	150mv
S/N	>95db
Frequency	20Hz-20KHz
Microphone Tone	80Hz+/-12db;12KHz+/-12db
Echo Tone	250Hz+/-12db,12KHz+/-12db
Over all Tone	80Hz+/-12db;2.5KHz+/-8db;2KHz+/-12db
Dimension	500x445x210mm



## KTV DSP Amplifier DSP Series

DSP series amplifier have reliable quality, best tone.  
Suitable for Karaoke room etc.

<b>Model</b>	<b>DSP-300</b>
<b>Unit Price</b>	<b>\$330.00</b>
Output power	2x300W
Mic input sensitivity	10mv
Input sensitivity	150mv
S/N	>95db
Frequency	20Hz-20KHz
Microphone Tone	80Hz+/-12db;12KHz+/-12db
Echo Tone	250Hz+/-12db,12KHz+/-12db
Over all Tone	80Hz+/-12db;2.5KHz+/-8db;2KHz+/-12db
Dimension	500x445x210mm





## Stereo Tube IPOD Amplifier HI Series

HI series Ipod amplifier have reliable quality, best tone. HI-122 is equipped IPOD remote control.



<b>Model</b>	<b>HI-122</b>
<b>Unit Price</b>	<b>\$442.00</b>
Output Power	2x12W
Sensitivity	200MV
Distortion Factor	<0.8%
S/N	89dB
Input	4 Groups
Output	2 Groups
Frequency	20Hz-55KHz
Dimension	420x375x140mm
Gross Weight	14kg



## Tube Amplifier(USB+SD Card+FM Radio) HI Series

HI series tube amplifier have reliable quality, best tone. HI-155 is equipped remote control.

<b>Model</b>	<b>HI-155</b>
<b>Unit Price</b>	<b>\$370.00</b>
Output Power	2x5W
Sensitivity	290MV
Distortion Factor	<0.8%
S/N	88dB
Input	PC.CD.USB.SD.MP3, Radio Headset
Output Impedance	8Ohm
Frequency	20Hz-45KHz
Dimension	420x350x290mm
Gross Weight	12kg



## Stereo Tube Amplifier (40W)HI Series

HI series tube amplifier have reliable quality, best tone. HI-140 is equipped remote control.

<b>Model</b>	<b>HI-140</b>
<b>Unit Price</b>	<b>\$530.00</b>
Output Power	2x40W
Sensitivity	200MV
Distortion Factor	<0.8%
S/N	90dB
Input	4 Groups
Output	2 Groups
Output Impedance	4ohm,8ohm
Frequency	18Hz-60KHz
Dimension	500x460x360mm
Gross Weight	25kg



## HI-FI Loudspeaker HI Series

HI series have reliable quality, best tone. HI-10 could work together with HI-122,HI-155,HI-140.

<b>Model</b>	<b>HI-10</b>
<b>Unit Price</b>	<b>\$88.88</b>
High driver	3/4Inch
RMS Power	HF:10W LF:40W
Sensitivity	90dB
Crossover	3.5KHz
Cutoff frequency	75Hz
Frequency	60Hz-20KHz
Output Impedance	4ohm,8ohm
Dimension	260x130x300mm
Gross Weight	13kg

